

GENERAL SPECIFICATIONS

| Models | Motor (HP) | Bore x Stroke (mm) | No. of Cyl. | Piston Displacement (cfm) | Free Air Delivery (acfm) | Speed (rpm) | Max. Working Pressure (psi) | Receiver (gal.) | Air Outlet (Inch) | Flywheel | | Weight (lbs) |
|--------------|------------|--------------------|-------------|---------------------------|--------------------------|-------------|-----------------------------|-----------------|-------------------|----------|------------|--------------|
| | | | | | | | | | | Type | Pitch Dia. | |
| CROF-001-U/P | 1 | 60 x 50 | 1 | 4.97 | 3.0 | 1000 | 100 | 20 | 3/8" Hose cock | A | 12-23/64" | 66 |
| CROF-002-U/P | 2 | 82 x 50 | 1 | 10.06 | 5.8 | 1080 | 100 | 30 | 3/8" Hose cock | B | 14-9/16" | 77 |
| CROF-003-U/P | 3 | 82 x 50 | 2 | 14.72 | 9.0 | 790 | 100 | 40 | 1/2" Ball valve | B | 14-9/16" | 99 |
| CROF-005-U/P | 5 | 90 x 60 | 2 | 23.20 | 15.2 | 860 | 100 | 40 | 1/2" Ball valve | 5V | 17-35/64" | 132 |
| CROF-075-U/P | 7.5 | 90 x 60 | 3 | 34.78 | 22.6 | 860 | 100 | 40 | 3/4" Ball valve | 5V | 17-63/64" | 172 |