

Horizontal Mount Type

- **Solid, cast iron construction**
- **Oversized bearings/crankcase**
- **Large Swedish steel valves**
- **Extreme durability**

Models	Motor (HP)	Piston Displacement (cfm)	Free Air Delivery (cfm)	Volts Phase	Pressure Setting (psig)	Air Receiver (Gal.)	Air Outlet (Inch)	Dimensions			Weight (lbs)
								Width	Depth	Height	
CRAC-D5H	5	20	16.0	230V/1Ph or 230/460V/3Ph	145-175	80	3/ 4"	70"	23"	44	520
CRAC-D7.5H	7.5	30	24.0	230/460V/3Ph	145-175	80	3/ 4"	70"	23"	44	550
CRAC-D10H	10	40	32.0	230/460V/3Ph	145-175	120	1"	70"	26"	52"	790
CRAC-D15H	15	60	48.0	230/460V/3Ph	145-175	120	1"	70"	28"	56"	835
CRAC-D20H	20	80	64.0	230/460V/3Ph	145-175	120	1"	70"	28"	66"	950

Vertical Mount Type

- **Cast iron pump**
- **High efficiency valves**
- **Maximum cfm to hp ratio**
- **100% ready to run**
- **Performance and durability**

Models	Motor (HP)	Piston Displacement (cfm)	Free Air Delivery (cfm)	Volts Phase	Pressure Setting (psig)	Air Receiver (Gal.)	Air Outlet (Inch)	Dimensions			Weight (lbs)
								Width	Depth	Height	
CRAC-D5V	5	20	16.0	230V/1Ph or 230/460V/3Ph	145-175	80	3/ 4"	36"	24"	70"	430
CRAC-D7.5V	7.5	30	24.0	230/460V/3Ph	145-175	80	3/ 4"	36"	24"	70"	530