

GENERAL SPECIFICATIONS

Models	Motor (HP)	Voltage (60Hz)	Phase	Ambient Temperature (°F)	Max. Working Pressure (psi)	Speed (rpm)	Free Air Delivery (cfm)		Noise Level dB(A)	Air Outlet (Inch)	V-Belt	Dimension (WxDxH)	Weight (lbs)
							@50 psi	@100 psi					
CROF-P(U)1	1	208-230 (460)	3(1)	32-104	100	1000	3.5	3.0	70	3/8"	A	35.7/8"x26"x31.1/2"	240
CROF-P(U)2	2	208-230 (460)	3(1)	32-104	100	1080	7.3	5.8	73	3/8"	B	35.7/8"x26"x31.1/2"	370
CROF-P(U)3	3	208-230 (460)	3(1)	32-104	100	790	10.7	9.0	74	3/8"	B	35.7/8"x26"x31.1/2"	430
CROF-P(U)5	5	208-230 (460)	3(1)	32-104	100	945	16.7	15.2	75	3/8"	5V	45.1/4"x26"x36.7/8"	540
CROF-P(U)7.5	7.5	208-230 (460)	3	32-104	100	860	25.5	22.6	77	3/8"	5V	45.1/4"x26"x36.7/8"	730

Note: Please consult with our sales representative 1 phase application.

Sound Pressure Level(SPL) are measured at 5 ft. from front of the unit.