

Job Name	Location
Purchaser	Engineer
Submitted to	Reference <input type="checkbox"/> Approval <input type="checkbox"/> Construction <input type="checkbox"/>
Unit Designation	Schedule #

Specifications	
General	
Nom Cooling Capacity (Btu/h)	24,000
SEER	13.0
Condensate Removal (Pints/hr)	5.3 pt/hr
Refrigerant Type	R410A
Power Voltage	208/230V-1Ph-60Hz
Breaker Size	20A
RLA Cooling/Heating (Amps)	8.8A
Controls	Wireless
Indoor Unit	
CIC-24M2Z	
Airflow-H-M-L Speed (CFM)	800 - 700 - 640
Fan Speeds	High-Med-Low
Noise Level H - M - L (Db)	52 - 48 - 45
Width (Inches)	49 1/4"
Height (Inches)	12 3/4"
Total Depth (Inches)	9"
Weight (lbs)	39.6lbs
Condensate Connection Ø	5/8" OD
Outdoor Unit	
COC-24M2Z	
Outdoor Noise Level (Db)	59
Width (Inches)	35 1/4"
Height (Inches)	33 7/8"
Total Depth (Inches)	13"
Weight (lbs)	149.6lbs
Line Sets	
Size	3/8" & 5/8"
Max Line Set Length inc	65ft
Max Vertical Separation of	33ft
Charged with R410A for	25ft
Standard R410A charge	90.7oz
Addl R410A charge required	0.7oz/ft
Certifications	
Safety	ETL & ETLc
Warranty	
	5 Years Compressor
	2 Year Parts
Options	
	25 or 50ft Line Sets
	Condensate Pumps
	Low Ambient



Construction

Indoor Unit shall be made from UL94 V0 HIPS
The Outdoor unit shall be galvanized steel with a baked on powder coated finish for durability

Heat Exchangers

The heat exchangers shall be mechanically bonded fin to copper tube. Fins shall have a hydrophilic coating

Refrigerant System

Compressors shall be a hermetically sealed Rotary type, with an external overload protector
Refrigerant shall be R410A.
Refrigerant flow shall be controlled by Capillary tube

Indoor Fan

The indoor unit fan shall be statically and dynamically balanced. An auto swing louver with dual blades shall direct airflow
The outdoor unit fan shall be a propeller type

Controls

The unit shall be operated via a wireless remote
Temperature setting range 63 DegF to 86 DegF
Control signal shall be a 0-5V AC signal
Indoor unit power supply is 208/230V AC
Wiring between Indoor & Outdoor shall be 14AWG
Unit operating range shall be
Cooling 65 DegF to 115 DegF Outdoor ambient
Cooling in ambients below 65 DegF is possible using the low ambient option

Air Filtration

Dual washable Air Filters shall be accessed via the hinged front panel